

# Uniphos Detector Tube Data Sheet

Direct Reading Length of Stain Type

## Hydrogen Chloride HCl

## SHC- 3

TWA (TLV): NA

Ceiling (TLV): 2 ppm

Non Flammable

### Specification:

	Extended	Standard	Extended
Measurement Range	2.5 – 50 ppm	5 – 100 ppm	10 – 200 ppm
No. of Pump Strokes	2 (200 mL)	1 (100 mL)	0.5 (50 mL)
Volume Correction Factor (VCF)*	0.5	1.0	2.0
Sampling Time	1 minute per pump stroke (100 mL)		
Color Change	Yellow → Pink		
Shelf Life	1 year		
Storage condition	Below 10°C (50°F)		
Calibration condition	Calibrated at 20°C (68°F) and 50% RH.		
Reaction Principle	HCl + Base → Reaction product		
Relative standard deviation	± 10 %		

\* Multiply the observed reading by the correction factor (VCF) to obtain the true concentration.

### Possible Interferences:

Compound	Concentration (ppm)	Interference	Colour change / Comments
Cl <sub>2</sub>		+	Yellow to Pink
HF		+	Yellow to Diffused Pink
NH <sub>3</sub>	100	No	No effect
NO <sub>2</sub>	200	No	No effect
H <sub>2</sub> S	100	No	No effect

### Correction for Environmental Parameters:

Temperature	Not necessary between 0 - 40°C (32 - 104°F).
Relative humidity	Not necessary between 10 - 90 %.



**Manufactured By:** Uniphos Envirotronic Pvt. Ltd.  
Nahuli (PO), Umbergaon (Tal.)  
Valsad (Dist), Gujarat, India – 396108

Rev.0812